



BUGSIER 5

ROTOR - TUG



MAIN DATA		DECK LAYOUT		NAV & RADIO EQUIPMENT	
Type:	Harbour, Stand By, Salvage	Bow Winch:	Plimsoll PC-HTW combined anchor/towing winch	ECDIS:	1 x Chartworld eGlobe
Built:	2008 / ASL SY PTE Singapore	Pull:	30 to	Radar:	2 x Furuno FAR 2117
Manager:	Bugsier-, Reederei- & Bergungs GmbH & Co. KG	Holding Force:	200 to	Gyro / THD:	Furuno SC-50
Owner:	Fairplay Towage	Drum 1:	150m / 80mm / T-Power	GPS:	Furuno GP 150
Class:	DNV +100 A5 M Tug DNV +MC AUT FIFi1	Drum 2:	-	AIS:	Furuno FA 150
Register & Flag:	Hamburg/Germany	Aft Winch:	Plimsoll PC-HTW Towing Winch	NAVTEX:	Furuno NX 700
DIMENSIONS		Pull:	30 t	Echo Sounder:	Furuno FE 700
Length over all:	28,00 m	Holding Force:	200 t	Autopilot:	Navitron
Breadth over all:	11,80 m	Drum 1:	150m / 80mm / T-Power	Speedlog:	Furuno Ds 80
Draft (min/max):	5,95 m / 6,20 m	Drum 2:	-	Handheld VHF:	2 x ICOM
Airdraft (min):	11 m (foldable from 17m)	Spare Wire:	-	FIFI & SAFETY	
GT / NT:	377/113	Tugger Winch:	-	Class:	Class 1 (1.200 m³/h)
PROPULSION SYSTEM		Stern Roller:	-	Foam Capacity:	33 m³
Type:	3x Rudder-Propeller	Karmforks:	-	Breathing App.:	4 Sets
Main Engines:	3x Wärtsilä 8L20	Tow Pins:	2 x	Rescue Boat:	DSB 420 + Mercury (25HP)
Total Power:	6825 HP / 4800 kW	Smit Bracket:	-	Rescue System:	-
Bow Thruster:	-	Crane:	Palfinger Marine 0,95 t @ 10m	COMMUNICATION	
Stern Thruster:	-	Deck Space:	-	Call Sign:	DDTL2
PERFORMANCES		Extensive equipment of shackles, wires, ropes and bridles for short sea and harbour towage.		IMO No.:	9376206
Bollard Pull:	max. 86 t ahead / 85,9 t astern	SPECIALS		MMSI No.:	218393000
Speed:	max. 12 kn / eco. 9 kn	ACCOMODATION		GSM:	0049 160 530 104 8
Cruising Range:	5 days	Cabins:	2 x Officer single berth cabin 2 x Crew double berth cabin	GSM Fax:	0049 160 537 692 2
Trade Area:	A1, A2	Total berths:	6	SAT FBB:	-
Consumption:	12 m³ / d - ECO-Speed	TANK CAPACITIES		Mail Port:	bugsier5@bugsier.de
MGO:	125 cbm (98 cbm)	MGO:	125 cbm (98 cbm)	Mail Sea:	-
Pot. Water:	18,00 m³	Pot. Water:	18,00 m³	SAT C (1):	-
Lub. Oil:	1,20 m³	Lub. Oil:	1,20 m³	SAT C (2):	-
Sludge:	2,60 m³	Sludge:	2,60 m³	Iridium:	-
Bilge Water:	5,10 m³	Bilge Water:	5,10 m³	Additional:	-
Sewage:	Sewage Plant	Sewage:	Sewage Plant	AUXILIARY SYSTEMS	
Auxiliary Engines:	2 x Volvo 4-stroke (139kW) 1 x Hatz 4-stroke (30 kW)	AUXILIARY SYSTEMS		Auxiliary Engines: 2 x Volvo 4-stroke (139kW) 1 x Hatz 4-stroke (30 kW)	

Particulars of this unit and inventory believed correct at time of printing but subject to change.
Printed June 2021 replacing all previously printed particulars