



# FAIRPLAY BANDAMA

## Tractor Tug

MAIN DATA	
Type :	Voith-Schneider Tractor
Call sign :	EBTG
Length over all :	30,54 m
Breadth over all :	11,00 m
Draft ( min/max ) :	5,18 m
GRT :	359 GT
Class :	GL + 100 A5 M E1 TUG + MC E1 AUT
Bollard Pull :	56 t
Airdraft (minimum) :	15,35 m t
Speed :	12,0 kn max / 9 kn Eco
Built :	1997
Capacities :	Fuel Oil Tks: 159,2 m <sup>3</sup> Fuel Oil Capa. 120 m <sup>3</sup> Pot Water Capa. 24 m <sup>3</sup> Pot Water Prod. 1,5 m <sup>3</sup> /d
Accommodation :	8 x berth
ENGINES	
Horsepower :	3.690 kW
Main Engines :	2 x Deutz SBV 9 M 628
Propulsion :	Twin – Voith – Propeller 28 G II / 210
TOWING GEAR	
Towing Equipment :	1 x waterfall double drum hydraulic towing winch: 23 t pull / 125 t breakhold 1 x drum 150 m / 42 mm dia. wire cap. 1 x drum 750m / 42 mm dia. wire cap. 1 x spare wire 750 m / 42 mm dia.

EQUIPMENT	
Equipment :	Ample supply of portable Dieselhydraulic and electric submersible pumps. Combined anchor / mooring winch with 2 mooring drums, 130 kN pull / 480 kN breakhold on foredeck 1 x capstan 66 kN pull on towing deck Deck crane on aft deck 0,6 t – 10 m Stern slide for anchor handling (Anchor cannot be taken on deck)
Bridge Equipment :	GMDSS A2 2 x VHF Mobile phone GSM DGPS 2 x Searchlight each 1000 W Gyro Compass 2 x Radar Echosounder Autopilot ECDIS Mag. Compass AIS Navtex LRIT
COMMUNICATION	
MMSI No. :	224091000

Extensive supply of spare wires, ropes, chains, shackles and bridles for deep-sea and harbour towage as well as salvage.

Particulars of this unit and inventory believed correct at time of printing but subject to change.  
Printed September 2020 replacing all previously printed particulars